



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 489 042 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
22.12.2004 Bulletin 2004/52

(51) Int Cl.7: **B67D 1/00**

(21) Application number: **04014363.8**

(22) Date of filing: **18.06.2004**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PL PT RO SE SI SK TR**
Designated Extension States:
AL HR LT LV MK

(72) Inventor: **Mobbs, Nigel**
Worcestershire WR7 4PF (GB)

(74) Representative: **Lucking, David John**
FORRESTER & BOEHMERT
Pettenkoferstrasse 20-22
80336 München (DE)

(30) Priority: **19.06.2003 GB 0314277**

(71) Applicant: **Whitlence Drink Equipment Limited**
Halesowen, West Midlands B62 8SE (GB)

(54) **Beverage dispensing system with automatic identifier of ingredient containers**

(57) A system 10 for dispensing a beverage which is a mixture of stock and water, includes a dispensing apparatus 11 having a water supply 25 thereto, and a container 12 containing the stock, the apparatus 11 further including a controller C which in use controls the apparatus 11 to mix water with the stock to make the beverage, and to deliver the beverage to a beverage

outlet 36, 36', and wherein the container 12 includes an identification device D which identifies the nature of the beverage to be dispensed, and the dispensing apparatus 11 includes a sensor S, S' which senses the identification device D and provides a signal to the controller C which identifies the nature of the beverage to be dispensed from the signal.




FIG. 1

EP 1 489 042 A1

Description

[0001] This invention relates to a system for dispensing a beverage which is a mixture of stock, such as a flavouring, colouring or the like which is to be diluted, and water.

[0002] Conventionally systems for dispensing a beverage, such as a soft drink, which is a mixture of a stock being syrup and water, have included a water supply, a syrup supply, a mixing device for mixing these together with an appropriate volume ratio of water to syrup, and a dispensing nozzle from where the mixed beverage is dispensed. The water supply, in most examples, has included some cooling apparatus for cooling the water, and also in most examples, a carbonating device for carbonating the beverage prior to its dispensing.

[0003] Particularly in outlets where only a small volume of beverage is dispensed, the cost of supplying the system and for maintaining the system, can far outweigh the possible profits to be made from selling beverage. Maintenance costs are high both to ensure that the correct proportions of water and syrup are consistently mixed, but also in the hygienic maintenance of the system, particularly in cleaning out the dispensing head from where the beverage is dispensed. Accordingly, in outlets which sell only a small volume of beverage, it is more attractive to retail bottled beverages.

[0004] Even though for a large conventional installation, some components, such as the cooling apparatus and/or carbonising apparatus where provided, may be shared, where different beverages are to be dispensed it is a requirement for an individual mixing device and dispensing nozzle, together with associated plumbing, to be provided for each different beverage. Where the outlet is a bar, the provision of a multitude of different dispensing nozzles can provide a logistics problem in accommodating them.

[0005] Moreover, the syrup for the or each beverage is provided in large volumes in syrup containers. Thus a conventional system cannot economically be used to dispense small volumes for example of a specialist beverage on a trial basis, without risking wasting a large volume of the syrup.

[0006] According to a first aspect of the invention we provide a system for dispensing a beverage which is a mixture of stock and water, the system including a dispensing apparatus having a water supply thereto, a container containing the stock, the apparatus further including a controller which in use controls the apparatus to mix water with the stock to make the beverage, and to deliver the beverage to a beverage outlet, and wherein the container includes an identification device which identifies the nature of the beverage to be dispensed, and the dispensing apparatus includes a sensor which senses the identification device and provides a signal to the controller which identifies the nature of the beverage to be dispensed from the signal.

[0007] Thus a wide variety of different beverages may

be dispensed by a user selecting an appropriate container which is identified by the dispensing apparatus so that the stock may be mixed with an appropriate volume and type of water in the apparatus, so that a desired beverage may be dispensed. Thus simply by selecting an appropriate container, a large, medium or small volume beverage may be dispensed for example, and/or a carbonated or a non-carbonated drink may be dispensed, and the water of the supply may be cooled or heated, all depending upon the identification device of the container.

[0008] In one embodiment, the identification device of the container may include a marking and the sensor is an optical sensor. Such a marking may be a bar code in which case the sensor is a bar code reader.

[0009] Additionally or alternatively the identification device may include a physical feature of the container, such as the shape of the container or the position and/or number of notches in a container wall for examples, the position(s) of which relative to the dispensing apparatus indicates the nature of the beverage to be dispensed by mixing water with the stock contained within the container, and in each case, the feature being sensed optically and/or physically by the sensor.

[0010] Preferably, to ensure proper registration between the identification device and the sensor, the dispensing apparatus and the container have inter-engaging formations which enable the container to be received by the apparatus in an operative position in which the identification device is sensed by the sensor.

[0011] In one arrangement, upon a user selecting a container for producing a desired beverage, the container is locatable in position upon the manual insertion of the container in the apparatus. However alternatively, the user may place the container in a position relative to the dispensing apparatus, and the container may be locatable in its operative position by a mechanical loading device which moves the container into the operative position where the sensor senses the identification device.

[0012] To provide a beverage of a volume selected by the user choosing a container appropriate to the desired volume, the controller may meter the water to provide a predetermined volume of water for mixing with the stock, in response to the signal from the sensor.

[0013] The system may include a gassifying device e.g. for carbonating the water, e.g. integrated into the dispensing apparatus, or provided remotely, and the controller may mix one of carbonated water and non-carbonated water with the stock, in response to the signal from the sensor. Thus a user may choose a container appropriate to obtain a carbonated or non-carbonated beverage.

[0014] At least part of the water supply to the apparatus may be a water supply from a cooling and/or heating unit wherein the controller mixes water in a predetermined temperature range with the stock, in response to the signal from the sensor, e.g. by mixing cooled or heat-

ed and non-cooled or non-heated water in appropriate quantities to achieve a water temperature within the predetermined temperature range.

[0015] In another arrangement, the dispensing apparatus may include a cooling and/or heating unit to change the temperature of the water of the supply, and wherein the controller mixes water in a predetermined temperature range with the stock, in response to the signal from the sensor.

[0016] In each case, a user may obtain beverage at a temperature appropriate for the nature of the beverage to be dispensed and according to the user's choice. For example a hot or cold fruit squash/juice drink may be dispensed.

[0017] If desired, the system may include an ice dispenser and in response to an appropriate signal from the sensor which indicates the user's choice of container is for an iced drink, the controller may dispense ice for the beverage on receipt of an appropriate signal from the sensor. The ice dispenser may be integrated with the dispenser apparatus or separate.

[0018] In one embodiment, the container may include a water inlet and the beverage outlet which are each sealed prior to receiving the container in the apparatus, and immediately prior to or upon receiving the container in the apparatus, the water inlet at least is unsealed to permit water to enter the container from the dispensing apparatus. The beverage outlet may become unsealed as pressure builds up within the container, as the water is fed into the container or otherwise, whereby the water and stock are mixed in the container as water flows from the water inlet to the beverage outlet, and the beverage is dispensed directly from the beverage outlet.

[0019] In another arrangement in which the stock may be emptied from the container, the water and stock are mixed as they each flow towards a beverage outlet of the apparatus. Thus the container may include a rupturable seal which is ruptured when the container is received by the apparatus to permit the stock to flow from the container.

[0020] In each case, the container may be disposable, automatically or manually, after its stock has been dispensed.

[0021] According to a second aspect of the invention we provide a method of using the system according to the first aspect of the invention, the method including selecting from a store of containers a container filled with stock appropriate for fulfilling a customer's order, inserting the container into the apparatus, the selected container having an identification device which identifies the nature of the beverage to be dispensed, sensing the identification device with the sensor and providing a signal to the controller which identifies from the signal the nature of the beverage to be dispensed, and dispenses the beverage depending upon the signal.

[0022] The method may include subsequently removing the container from the apparatus and disposing of the container.

[0023] According to a third aspect of the invention we provide a container for use in a beverage dispensing system according to the first aspect of the invention wherein the container includes stock to be diluted with water from the dispensing apparatus, and an identification device to identify the nature of the beverage to be dispensed, the identification device being readable by the sensor of the apparatus.

[0024] Embodiments of the invention will now be described with reference to the accompanying drawings in which:-

FIGURE 1 is an illustrative side view of a beverage dispensing system in accordance with the first aspect of the invention;

FIGURES 2a and 2b are illustrative perspective views of a beverage dispensing apparatus of a system in accordance with the invention in different stages of use;

FIGURES 3a to 3c are illustrations of alternative kinds of container for use in the system of the present invention.

[0025] Referring first to figure 1, there is shown a system 10 for dispensing a selected one of a plurality of different beverages, each beverage being a mixture of a flavouring, colouring or the like, for example stock, which is to be diluted, and water. In the example to be described, the stock is a syrup which when mixed with water, in this example which may be cooled and/or carbonated water, provides a beverage which is a so called "soft drink". However the stock need not be a liquid but may be a solute or other flavouring and/or colouring, or may for example be a mixture of health enhancing salts and minerals.

[0026] The system 10 includes a beverage dispensing apparatus 11, and a container 12 for syrup. The apparatus 11 is shown mounted on a bar 13, and includes a housing 14 in which in use the container 12 is received, and from which beverage is dispensed into a drinking vessel 15 which may be supported on a shelf 16 of the apparatus 11 as shown, at a point of beverage delivery.

[0027] Beneath the bar 13 in the housing 14, there is provided in this example a cooling unit 18 including a reservoir of a cooling liquid 19, which is cooled by expanded refrigerant, or another cooled fluid which passes through the reservoir 19 in one or more cooling coils 20. The reservoir 19 is within a highly insulated bath, and typically in use an ice bank 22 is created around the cooling coil(s) 20.

[0028] Water is supplied to the cooling unit 18 from a water inlet 25, and as hereinafter explained, the water passes along a feed line 24, through the reservoir of cooled liquid, to a conduit 26 which extends to a water outlet 28 above the shelf 16. Within the reservoir 19 there is located a carbonating device 30 to which a supply of pressurised carbon dioxide is fed along a gas conduit 31 from externally of the apparatus 11. In the car-

bonating device 30, the water may be carbonated as it is cooled, as it flows in the feed line 24 to the conduit 26 towards the water outlet 28.

[0029] The refrigerant for cooling the reservoir 19 of the cooling unit 18, may be refrigerated by a local compression pump 32 and evaporator 33 as indicated, or may be located remotely from the beverage dispensing apparatus 18, e.g. in a cellar, and the refrigerant pumped to the cooling coils 20. Further alternatively, the entire cooling unit 18 may be located externally of the dispensing apparatus 11, for example to supply cooled water to the apparatus, and/or the carbonating unit 30 may be provided externally of the dispensing apparatus 11.

[0030] Along the conduit 26 for the water (which may optionally be cooled and carbonated as hereinafter described), between the cooling unit 18 and the water outlet 28, there is provided a control valve 34, the operation of which may be controlled by a controller C, to meter water permitted to pass to the water outlet 28, during dispensing of the beverage, the water flow along the conduit 26 being measured by a metering sensor M.

[0031] Referring to figures 2a and 2b, a part only of the beverage dispensing apparatus 11 is illustrated more figuratively. In this example, the container 12 is a flexible walled sachet which contains a predetermined quantity of the syrup, the container 12 having a water inlet 35, and a beverage outlet 36. The beverage dispensing apparatus 11 includes a mechanical container loading device 40 which includes a moveable flap 37 which may be opened as illustrated in figure 2a, to allow the container 12 manually to be inserted into the apparatus 11. As the flap 37 is closed, the container 12 is received in an operative position, such that the water inlet 35 is located immediately below the water outlet 28 of the apparatus 11. In fact, the outlet 38 preferably has a spout which during the loading action, causes the water inlet 35 which up until now has been sealed, to be ruptured.

[0032] The user may then operate a "dispense" control 38 (but operation of the apparatus 11 may be automatic when the presence of the sachet 12 is determined), and as a result the controller C opens the control valve 34 for a predetermined time and/or a predetermined amount only, but preferably until the metering sensor M determines that a predetermined volume of water has been dispensed, to dispense a metered volume of water from the water outlet 28.

[0033] The water is constrained to flow into the water inlet 35 of the container 12, and as a result the build-up of pressure in the container 12 may cause the up until now sealed beverage outlet 36 to be ruptured, so that the mixed syrup and water flow directly from the container 12 through the beverage outlet 36, into the drinking vessel 15 positioned below. Alternatively, the apparatus may include a device positively to rupture the beverage outlet seal 36 to allow the water to flow through the container 12, but in each case mixing of the syrup

and water will occur in the container 12 as the water and syrup flow.

[0034] After the metered volume of water has been dispensed, the flap 37 may be opened and the now empty container 12 automatically or manually disposed of, although of course it is within the scope of the present invention for the action of opening of the flap 37 to result in the mechanical removal of the container 12, for example into a waste receptacle.

[0035] It will be appreciated that a container 12 may be selected from a store of containers which may contain different syrups or other stock, which may be alternatively dispensed as appropriate to fulfil a customer's order. For example, containers 12 containing the same or different stock may require different metered volumes of water to be dispensed, and/or in some instances for the water not to be carbonated or cooled or heated to a temperature within a predetermined temperature range. Further alternatively, different containers 12 may contain the same volume of the same stock, but the containers 12 may indicate upon them different conditions under which the beverage is to be dispensed, i.e. cooled, heated, carbonated or non-carbonated. Thus the containers 12 of the store may have human readable markings relating to the nature of the beverage to be dispensed, and the conditions under which the beverage is to be dispensed, or such containers may be differentiated by being stored e.g. in individual bins for particular beverage types, from which a user selection may be made.

[0036] Each container 12 include an identification device D appropriate for identifying to a machine sensor S, the nature of the beverage to be dispensed using the individual container 12. Thus the fact that a user may have selected a container 12 for obtaining a cooled, carbonated medium volume beverage, may be identified to the machine sensor S by the identification device D.

[0037] Thus preferably, as or when the container 12 is received in the beverage dispensing apparatus 11, the sensor S senses the identification device D and provides an appropriate signal to the controller C.

[0038] Thus different containers 12 having different stock/beverage dispensing conditions, may be marked, for example with a bar code such as shown at 50 in figures 3a and 3b, or the container may be physically configured in particular shapes, so that the sensor S may recognise the identification device D and provide an appropriate input signal to the apparatus controller C.

[0039] In figure 3b there is indicated in dotted lines a physical shape sensor S' which senses the shape of the (bottle shaped) container 12 and particularly senses whether the container 12 is a large container 12 (indicated as in dotted lines) for containing a large volume of syrup or other stock for dispensing a large volume beverage, or a small container 12 (indicated in full lines) for containing a smaller volume of stock for dispensing a smaller volume beverage.

[0040] Alternatively in figure 3c, the an optical sensor

S optically senses a physical feature of the container 12, namely the position/size of a notch 55 which is indicative of the nature of the stock and/or the conditions under which the beverage is to be dispensed. Such a notch may alternatively be recognisable by a physical sensor such as a mechanical feeler S'.

[0041] In each case, the sensor S/S' may sense the identification device 50/55, which may include a marking such as bar code 50 in addition to a physical feature such as notch 55 if desired, and provide an appropriate signal to the controller C.

[0042] The controller C, from the signal from the sensor S/S', may determine the nature of the stock in the user selected container 12 loaded into the apparatus 11, or at least determines the nature of the desired beverage to be dispensed into the cup 15.

[0043] Examples of the dispensing of different beverages will now be given by way of further explanation.

[0044] In the event that a user selects a container 12 appropriate for dispensing a large volume of cooled carbonated drink such as a cola, the selected container 12 will have an appropriate identification device D to differentiate it from alternative containers 12.

[0045] The sensor S/S' upon sensing the identification device D will signal the controller C, which in response provides for a predetermined volume of cooled and carbonated water (by e.g. metering the water passing) to be passed along conduit 26 for mixing with the stock, so that the selected cooled carbonated beverage is dispensed into the cup 15.

[0046] In the event that a user selects a different container 12 appropriate for dispensing a smaller volume of cooled but un-carbonated drink, such as a fruit squash or juice, the selected container 12 will again have an appropriate identification device D.

[0047] The sensor S/S' upon sensing the identification device D will signal controller C which in response provides a smaller predetermined volume of cooled water along conduit 26. The controller C may render the carbonating device 30 inoperative, for example by allowing the water supply to by-pass the carbonating device 30, or by closing a valve 44 from the external gas supply 31, for examples only.

[0048] In the event that a user selects a different container 12 appropriate for dispensing a certain volume of beverage, which may be neither carbonated nor cooled, or only slightly cooled, e.g. an energy drink, the selected container 12 will have an appropriate identification device D.

[0049] The sensor S/S' upon sensing the identification device D will signal controller C which in response provides the predetermined volume of water for mixing with the stock, whilst by-passing the carbonating device 30 or closing the gas valve 44, and only passing a proportion (or none) of the water through the cooling unit 18, for example opening a by-pass valve 42. Thus by monitoring the temperature of the water flowing along the conduit 26, e.g. by a temperature sensor T, water

within a predetermined temperature range may be provided for mixing with the stock appropriate for the selected beverage.

[0050] Other means of controlling the extent of cooling and/or carbonation may be utilised. Indeed in another example, the temperature of water supplied may be increased by a heater unit to bring the temperature of the water provided for mixing with the stock to an appropriate temperature for a selected beverage to be dispensed, as identified by an appropriate identification device D.

[0051] Various modifications may be made without departing from the scope of the invention. For example, the water may be gassified by another gas than carbon dioxide, for example by oxygen, to provide a gassified beverage with may have energy level enhancing properties.

[0052] The apparatus 11 need not include a cooling unit 18 or carbonating or other gassifying device 30 which may be provided remotely, particularly where a common cooling unit 18 and gassifying device 30 are provided to supply cooled and/or gassified water to a plurality of beverage dispensing apparatus 11, e.g. in a commercial environment.

[0053] In figure 3b a container 12 is shown which does not include a beverage outlet 36. With this kind of container 12, the container 12 may be inverted in the apparatus 11, and a rupturable seal 35, e.g. a foil cap, may be ruptured to allow the stock contents of the container 12 to flow from the container 12 for mixing with the water, e.g. when flowing with the water to a beverage outlet 36' (see figure 1) from the dispensing apparatus 11.

[0054] In figure 3c the container 12 shown has a rigid wall 56 in which there is an opening closed by a foil seal 36. A notch 55 is provided at an appropriate position in the wall 56 to identify the nature of the beverage to be dispensed when the container 12 is used.

[0055] The container 12 includes a chamber 58 containing stock to release the stock, closed by the foil seal 36 which is ruptured in the apparatus 11, e.g. upon introducing the container 12 into the apparatus 11, and the stock is tipped out, or flushed out by the water, and mixed with the water as they each flow to the beverage outlet 36' of the apparatus 11.

[0056] The example of mechanical loading device 40 for the containers 12 is only exemplary. In another embodiment, the container 12 may be received in and mounted by the apparatus 11 manually, but in each case, inter-engaging formations of the container 12 and the apparatus 11 may ensure proper registry of the container 12 with the sensor S/S' to enable the identification device to be identified.

[0057] In figure 1, there are illustrated further optical sensors V1 and V2 adjacent the beverage outlet 36'. These may be provided to detect the presence of the cup 15, and to enable different sized cups 15 to be identified. Thus in the event that a large volume beverage is selected by a user, but a small volume cup 15 only is

placed to receive the beverage, the controller C may be programmed not to dispense the beverage but to provide a warning to the user that a larger cup 15 is required.

[0058] One or more than two such sensors V1 and V2 may be provided to distinguish between different size/configuration cups 15 as required.

[0059] The identification devices D of the containers 12 may identify the actual kind of beverage to be dispensed and if desired the dispensing apparatus 11 may include a display to confirm to a user the kind of beverage to be dispensed and the conditions of dispensing e.g. the volume, temperature range and whether carbonated or not, of the beverage.

[0060] Although as described, the beverage dispensing apparatus 11 has been provided on a bar 13, the apparatus 11 may be a free standing apparatus, and particularly where provided with an integral cooling unit 18 and gassifying device 30, the apparatus 10 may be adapted for use in a domestic environment so that a domestic user may make at home, soft drinks using containers of syrup, or other beverages, and thus avoid the need to carry from the shops volumes of such beverages which are, in the main, water.

[0061] If desired, by selecting an appropriate container 12 from the store, a user may select an iced beverage, in which case the controller C may operate an ice dispenser I which may be located in the dispensing apparatus 11 near to the cup 15, the controller C providing less water for mixing with the stock to compensate for the cup 15 volume occupied by the dispensed ice.

[0062] The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms hereof.

Claims

1. A system (10) for dispensing a beverage which is a mixture of stock and water, the system (10) including a dispensing apparatus (11) having a water supply (25) thereto, a container (12) containing the stock, the apparatus (11) further including a controller (C) which in use controls the apparatus (11) to mix water with the stock to make the beverage, and to deliver the beverage to a beverage outlet (36, 36'), and wherein the container (12) includes an identification device (D) which identifies the nature of the beverage to be dispensed, and the dispensing apparatus (11) includes a sensor (S, S') which senses the identification device (D) and provides a signal to the controller (C) which identifies the nature of the beverage to be dispensed from the sig-

nal.

2. A system according to claim 1 **characterised in that** the identification device (D) of the container (12) includes a marking and the sensor (S, S') is an optical sensor.
3. A system according to claim 1 or claim 2 **characterised in that** the identification device (D) includes a physical feature (55) of the container (12) which is sensed by the sensor (S, S').
4. A system according to any one of the preceding claims wherein the container (12) is locatable in an operative position upon the manual insertion of the container in the apparatus (11), or by a mechanical loading device (40) which moves the container (12) into the operative position where the sensor (S, S') senses the identification device (10).
5. A system according to any one of the preceding claims **characterised in that** controller (C) meters the water to provide a predetermined volume of water for mixing with the stock, in response to the signal from the sensor (S, S').
6. A system according to any one of the preceding claims which includes a gassifying device (30) for carbonating the water, and the controller mixes one of carbonated water and non-carbonated water with the stock, in response to the signal from the sensor (S, S').
7. A system according to any one of claims 1 to 6 **characterised in that** the dispensing apparatus (11) includes a cooling (30) and/or heating unit to change the temperature of the water of the supply, and wherein the controller (C) mixes water in a predetermined temperature range with the stock, in response to the signal from the sensor (S, S').
8. A system according to any one of the preceding claims **characterised in that** the container (12) includes a water inlet (35) and the beverage outlet (36) which are each sealed prior to receiving the container (12) in the apparatus (11), and immediately prior to or upon receiving the container (12) in the apparatus (11), the water inlet (35) at least is unsealed to permit water to enter the container (12) from the dispensing apparatus (11), the beverage outlet (36) becoming unsealed as pressure builds up within the container (12), as the water is fed into the container (12), whereby the water and stock are mixed in the container (12) as water flows from the water inlet (35) to the beverage outlet (36), and the beverage is dispensed directly from the beverage outlet (36).

9. A system according to any one of claims 1 to 7 **characterised in that** the water and stock are mixed as they each flow towards a beverage outlet (36') of the apparatus (11), the container (12) including a rupturable seal (36) which is ruptured when the container (12) is received by the apparatus (11) to permit the stock to flow from the container (12). 5
10. A system according to any one of the preceding claims **characterised in that** the container (12) is disposable after its stock has been dispensed. 10
11. A method of using the system (10) according to any one of the preceding claims which includes selecting from a store of containers (12) a container filled with stock appropriate for fulfilling a customer's order, inserting the container (12) into the apparatus (11), the selected container (12) having an identification device (D) which identifies the nature of the beverage to be dispensed, sensing the identification device (D) with the sensor (S, S') and providing a signal to the controller (C) which identifies from the signal the nature of the beverage to be dispensed, and dispenses the beverage depending upon the signal. 15
20
25
12. A container for use in a beverage dispensing system according to any one of claims 1 to 10 **characterised in that** the container (12) includes stock to be diluted with water from the dispensing apparatus (11), and an identification device (D) to identify the nature of the beverage to be dispensed, the identification device (D) being readable by the sensor (S, S') of the apparatus (11). 30
35

40

45

50

55






FIG. 1






FIG. 3a




FIG. 3b




FIG. 3c



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 04 01 4363

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 842 603 A (ROMANYSZYN JR MICHAEL T ET AL) 1 December 1998 (1998-12-01)	1-5,7,9-12	B67D1/00
Y	* column 2, line 61 - line 67 *	6,8	
	* column 5, line 22 - line 28 *		
	* column 6, line 9 - line 18 *		
	* column 7, line 33 - line 43 *		
X	US 5 312 017 A (ROMANYSZYN JR MICHAEL T ET AL) 17 May 1994 (1994-05-17)	1-5,7,9-12	B67D
	* column 2, line 30 - column 3, line 53 *		
Y	EP 0 947 518 A (GELATO QUICK S A S DI A GIORGE) 6 October 1999 (1999-10-06)	6	
	* paragraph [0024] *		
Y	US 3 628 444 A (MAZZA LAMBERTO) 21 December 1971 (1971-12-21)	8	
	* column 2, line 21 - line 55; figures 1,3 *		
<div style="text-align: center;">-----</div>			
<div style="text-align: center;">-----</div>			
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 23 September 2004	Examiner Desittere, M
<div style="display: flex; justify-content: space-between;"> <div> <p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone</p> <p>Y : particularly relevant if combined with another document of the same category</p> <p>A : technological background</p> <p>O : non-written disclosure</p> <p>P : intermediate document</p> </div> <div> <p>T : theory or principle underlying the invention</p> <p>E : earlier patent document, but published on, or after the filing date</p> <p>D : document cited in the application</p> <p>L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p> </div> </div>			

EPO FORM 1503 (01.02.2004) (P/ALC01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 04 01 4363

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

23-09-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5842603	A	01-12-1998	US 5494193 A	27-02-1996
			US 5305923 A	26-04-1994
			AU 6238096 A	29-11-1996
			WO 9636556 A1	21-11-1996
			US 2003000964 A1	02-01-2003
			US 6460734 B1	08-10-2002
			US 5615801 A	01-04-1997
			US 5735436 A	07-04-1998
			US 5312017 A	17-05-1994
			AU 2251992 A	12-01-1993
			BR 9206139 A	06-12-1994
			CA 2111478 A1	23-12-1992
			EP 0587803 A1	23-03-1994
			IE 921930 A1	16-12-1992
			JP 6508328 T	22-09-1994
			KR 203786 B1	15-06-1999
			WO 9222493 A1	23-12-1992
			AU 647805 B2	31-03-1994
			AU 8085091 A	31-12-1991
			BR 9106533 A	25-05-1993
			CA 2084646 A1	07-12-1991
			EP 0531423 A1	17-03-1993
			WO 9118826 A2	12-12-1991
US 5312017	A	17-05-1994	US 5305923 A	26-04-1994
			BR 9306356 A	30-06-1998
			CA 2118232 A1	25-11-1993
			EP 0639155 A1	22-02-1995
			JP 3228747 B2	12-11-2001
			JP 7507984 T	07-09-1995
			KR 256424 B1	15-05-2000
			MX 9302809 A1	31-05-1994
			WO 9323327 A1	25-11-1993
			AU 2251992 A	12-01-1993
			BR 9206139 A	06-12-1994
			CA 2111478 A1	23-12-1992
			EP 0587803 A1	23-03-1994
			IE 921930 A1	16-12-1992
			JP 6508328 T	22-09-1994
			KR 203786 B1	15-06-1999
			WO 9222493 A1	23-12-1992
			US 5494193 A	27-02-1996
			US 2003000964 A1	02-01-2003
			US 5615801 A	01-04-1997
			US 5842603 A	01-12-1998
			US 6460734 B1	08-10-2002

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 04 01 4363

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

23-09-2004

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5312017 A		US 5735436 A	07-04-1998
EP 0947518 A	06-10-1999	EP 0947518 A1	06-10-1999
US 3628444 A	21-12-1971	AT 298282 B	25-04-1972
		BE 743328 A	28-05-1970
		CH 519893 A	15-03-1972
		DE 1961052 A1	02-07-1970
		DK 136856 B	05-12-1977
		ES 374203 A1	16-12-1971
		FR 2026428 A5	18-10-1970
		GB 1228114 A	15-04-1971
		IE 34677 B1	23-07-1975
		JP 49009756 B	06-03-1974
		LU 60035 A1	17-02-1970
		MT 635 A	18-05-1970
		NL 6918882 A	22-06-1970
		NO 125047 B	10-07-1972
		OA 3188 A	15-12-1970
		SE 378409 B	01-09-1975

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82